

Film Capacitors

Weights

Date: May 2009

Weights

The following table contains the weights for all **radial-lead capacitors (2 pins) with plastic casings**.

Deviations of up to approximately $\pm 30\%$ are possible.

Lead spacing/ Type number	Dimensions w × h × l mm	Weight g
Lead spacing 5 mm		
B32529,	2.5 × 6.5 × 7.2	0.20
B32559	3.0 × 6.5 × 7.2	0.25
	3.5 × 8.0 × 7.2	0.32
	4.5 × 9.5 × 7.3	0.46
	5.0 × 10.0 × 7.5	0.54
	6.0 × 10.5 × 7.5	0.68
	7.8 × 13.0 × 7.8	0.90
Lead spacing 7.5 mm		
B32520,	2.5 × 7.0 × 10.0	0.30
B32620	3.0 × 8.0 × 10.0	0.40
	4.0 × 8.5 × 10.0	0.52
	5.0 × 10.5 × 10.0	0.80
	6.0 × 12.0 × 10.3	0.98
Lead spacing 10 mm		
B32021, B32521,	4.0 × 7.0 × 13.0	0.52
B32591, B32601,	4.0 × 9.0 × 13.0	0.70
B32621, B32651,	5.0 × 11.0 × 13.0	1.1
B32671,	6.0 × 12.0 × 13.0	1.4
B32911, B32921		
Lead spacing 15 mm		
B32022, B32522,	5.0 × 10.5 × 18.0	1.5
B32572, B32592,	6.0 × 11.0 × 18.0	1.9
B32602,	6.0 × 12.0 × 18.0	2.1
B32612, B32632,	7.0 × 12.5 × 18.0	2.5
B32652, B32672,	8.0 × 14.0 × 18.0	3.2
B32912, B32922,	8.5 × 14.5 × 18.0	3.3
B81123	9.0 × 17.5 × 18.0	4.5
	11.0 × 18.5 × 18.0	5.6
	13.0 × 14.0 × 18.0	4.1

Lead spacing/ Type number	Dimensions w × h × l mm	Weight g
Lead spacing 22.5 mm		
B32023, B32523,	6.0 × 15.0 × 26.5	4.0
B32573, B32593,	7.0 × 16.0 × 26.5	4.8
B32613, B32633,	7.5 × 14.0 × 26.5	4.7
B32653, B32673,	8.5 × 16.5 × 26.5	5.5
B32913, B32923,	9.0 × 14.0 × 26.5	5.6
B81123	10.5 × 16.5 × 26.5	7.5
	10.5 × 18.5 × 26.5	8.0
	10.5 × 20.5 × 26.5	8.5
	11.0 × 20.5 × 26.5	9.0
	12.0 × 22.0 × 26.5	10.5
	14.5 × 29.5 × 26.5	18.9
Lead spacing 27.5 mm		
B32024	11.0 × 19.0 × 31.5	9.5
B32524, B32594,	11.0 × 21.0 × 31.5	10
B32614, B32634,	12.5 × 21.5 × 31.5	13
B32654, B32674,	13.5 × 23.0 × 31.5	15
B32774,	14.0 × 24.5 × 31.5	16
B32914, B32924	15.0 × 24.5 × 31.5	16
	16.0 × 32.0 × 31.5	21
	18.0 × 27.5 × 31.5	20
	18.0 × 33.0 × 31.5	24.5
	19.0 × 30.0 × 31.5	23
	21.0 × 31.0 × 31.5	26.3
	22.0 × 36.5 × 31.5	33
Lead spacing 37.5 mm		
B32026, B32526,	12.0 × 22.0 × 42.0	18
B32656, B32676	14.0 × 25.0 × 42.0	20
B32686A,	16.0 × 28.5 × 42.0	25
B32776,	18.0 × 32.5 × 41.5	32
B32916, B32926	20.0 × 39.5 × 41.5	40
	20.0 × 39.5 × 42.0	40
	28.0 × 42.5 × 41.5	60
Lead spacing 52.5 mm		
B32678, B32778	30.0 × 45.0 × 57.5	90
B32928	35.0 × 50.0 × 57.5	120

Weights

SilverCap™

Lead spacing/ Type number	Dimensions w × h × l mm	Weight g
Lead spacing 7.5 mm		
B32560	9.8 × 11.0 × 9.0	0.98
Lead spacing 10 mm		
B32561	8.8 × 13.3 × 11.0	1.45
Lead spacing 15 mm		
B32562, B32572	13.9 × 14.5 × 16.5	3.90

Lead spacing/ Type number	Dimensions w × h × l mm	Weight g
Lead spacing 22.5 mm		
B32563, B32573	12.8 × 17.2 × 24.0	6.67
Lead spacing 27.5 mm		
B32564	16.0 × 20.0 × 29.0	11.24