
越峰電子材料股份有限公司			客戶規格編號(Customer Spec.No.)	
ACME Electronics Corporation				
客戶特殊規格書	品名: (Part No.)	客戶名稱 (Customer)	生效日期(Effect	rive Date)
(Customer Specification)	A05UT15.4C			
客戶料號(Customer Part No.):			版次(Version) 第一版	



# 塗裝后尺寸規格Coating Dimensions (mm)-C:

A	В	С	Е	F
15.80±0.30	14.2max	7.30±0.30	9.80min	7.70min
塗裝前尺寸規格 Dimensions (mm):				
А	В	С	Е	F
15.40±0.30	13.40±0.20	6.90±0.20	10.50±0.20	8.55±0.20

# 電磁特性規格 (Electrical Characteristics):

# 高导材質 (High $\mu$ i Materials)

材質	初導磁率	電感(Inductance)	耐電壓
(Material)	μi	AL(nH/N²)	(BreakdownVoltage)
A05	5000±25%	2000min	1500 VDC min

## AL need to be actually measured

# 測試條件(Testing Condition):

	電感係數(Inductance Factor)	耐電壓(Breakdown Voltage)
測試條件 Condition	10kHz,50mV	
測試儀器 Equipment	卡尺(callipers)/HP4284A	054 10
室溫 Temperature	25°C±3°C;	0.5mA,1Sec
線圈 COIL	0.5mm,1Ts(ACME)	

### REMARK:

- 1. Color No. 349C
- 2.AL need to be actually measured

核准(Approved by):	審查(Checked by):	制定(Prepared by):	頁次(Page)1/1
		Lily Guo	KS