



越峰電子材料股份有限公司 ACME Electronics Corporation			客戶規格編號(Customer Spec.No.)																			
客戶特殊規格書 (Customer Specification)	品名: (Part No.) P41T12.7*7.14*6.35C	客戶名稱 (Customer) Platan	生效日期(Effective Date)																			
客戶料號(Customer Part No.):			版次(Version) 第一版																			
 																						
塗裝後尺寸規格Coating Dimensions (mm)-C:			塗裝前尺寸規格 Dimensions (mm):																			
<table><tr><td>A</td><td>C</td><td>E</td></tr><tr><td>13.7max</td><td>7.25max</td><td>6.24min</td></tr><tr><td>Ae</td><td>Le</td><td>Ve</td></tr><tr><td>17.17 mm²</td><td>29.51 mm</td><td>506.7 mm³</td></tr></table>			A	C	E	13.7max	7.25max	6.24min	Ae	Le	Ve	17.17 mm ²	29.51 mm	506.7 mm ³	<table><tr><td>A</td><td>C</td><td>E</td></tr><tr><td>12.7±0.4</td><td>6.35±0.3</td><td>7.14±0.3</td></tr></table>		A	C	E	12.7±0.4	6.35±0.3	7.14±0.3
A	C	E																				
13.7max	7.25max	6.24min																				
Ae	Le	Ve																				
17.17 mm ²	29.51 mm	506.7 mm ³																				
A	C	E																				
12.7±0.4	6.35±0.3	7.14±0.3																				
電磁特性規格 (Electrical Characteristics):																						
低鐵損材質 (Low loss Material)																						
材質 (Material)	初導磁率 μi	電感(Inductance) AL(nH/N²)	耐電壓 (BreakdownVoltage)																			
P41	2400±25%	1700±25%	1500 VDC min																			
AL need to be actually measured																						
測試條件(Testing Condition):																						
	電感係數(Inductance Factor)	耐電壓(Breakdown Voltage)																				
測試條件 Condition	10kHz,50mV	0.5mA,1Sec																				
測試儀器 Equipment	卡尺(callipers)/HP4284A																					
室溫 Temperature	25°C±3°C;																					
線圈 COIL	0.5mm,1Ts(ACME)																					
REMARK:																						
1. Color No. 349C																						
2.AL need to be actually measured																						
核准(Approved by):	審查(Checked by):	制定(Prepared by): Lily Guo	頁次(Page)1/1 KS																			