





## 5A-20A 应用于电机

产品图片 (Picture)				
产品图纸 (Drawing)				
产品型号 (Item No)	MR30-M. G. Y $\Psi$ L C E	MT30-M. G. Y $\Psi$ L C E	MR30PB30-M. G. Y $\Psi$ L C E	MR30PW20-M. G. Y $\Psi$ L C E
	MR30-M. N. B $\Psi$ L C E	MT30-M. N. B $\Psi$ L C E	MR30PB30-M. G. B $\Psi$ L C E	MR30PW20-M. G. B $\Psi$ L C E
		MT30-M. G. B $\Psi$ L C E	MR30PB30-M. G. BL $\Psi$ L C E	MR30PW30-M. G. Y $\Psi$ L C E
				MR30PW30-M. G. BL $\Psi$ L C E

### 产品电气参数 (Parameter)

耐电压 (Withstand voltage)	DC 500V			
额定电流 (Rated current)	15A/18#		15A	
瞬时电流 (Maxted current)	30A/18#		30A	
接触电阻 (Contact resistance)	1.20m $\Omega$			
插拔寿命 (Use times)	100times			
防打火 (Fireproof)	否			
带卡扣 (Buckle)	否			
接线推荐 (Connection recommendation)			PCB 板焊接标准 (PCB Board Welding Standard)	
AWG	温升 60 $^{\circ}$ C	温升 85 $^{\circ}$ C	PCB 板 + 焊盘厚度 : 1.0-1.2mm	焊脚高度 2.0mm
16#	20A	25A	PCB 板 + 焊盘厚度 : 1.6-2.0mm	焊脚高度 3.0mm
18#	15A	20A		
20#	10A	15A		