






## 20A-40A 应用于锂电池

产品图片 (Picture)					
产品图纸 (Drawing)					
产品型号 (Item No)	XT60-F. G. Y $\text{CE}$ XT60-F. G. B $\text{CE}$ XT60-F. G. BL $\text{CE}$	XT60U-F. G. Y $\text{UL CE}$ XT60U-F. N. B $\text{UL CE}$ XT60U-F. G. B $\text{UL CE}$	XT60PB30-F. G. Y $\text{CE}$	XT60PW30-F. G. Y $\text{UL CE}$	XT60PT-F. G. Y $\text{UL CE}$

产品电气参数 (Parameter)				
耐电压 (Withstand voltage)	DC 500V			
额定电流 (Rated current)	20A/16#			20A
瞬时电流 (Maxted current)	40A/16#			40A
接触电阻 (Contact resistance)	0.60mΩ			
插拔寿命 (Use times)	100times			
防打火 (Fireproof)	否			
带卡扣 (Buckle)	否			
接线推荐 (Connection recommendation)			PCB 板焊接标准 (PCB Board Welding Standard)	
AWG	温升 60°C	温升 85°C	PCB 板 + 焊盘厚度 : 1.6-2.0mm	焊脚高度 3.0mm
12#	40A	45A		
14#	30A	35A		
16#	25A	30A		