

40A-60A 应用于锂电池

产品图片 (Picture)				
产品图纸 (Drawing)				
产品型号 (Item No)	XT90H-F. G. Y ULCE	XT90S-F. G. Y UL	XT90PB30-F. G. Y ULCE	XT90PW30-F. G. Y UL
	XT90H-F. G. B ULCE		XT90PB30-F. N. B ULCE	XT90PW30-F. N. B
	XT90H-F. N. B ULCE			

产品电气参数 (Parameter)				
耐电压 (Withstand voltage)	DC 500V	DC 48V/ 等效电容 $\leq 2600\mu\text{F}$	DC 500V	
额定电流 (Rated current)	30A/12#		30A	
瞬时电流 (Maxted current)	60A/12#		60A	
接触电阻 (Contact resistance)	0.40m Ω			
插拔寿命 (Use times)	100times			
防打火 (Fireproof)	否	是	否	
带卡扣 (Buckle)	否			
接线推荐 (Connection recommendation)			PCB 板焊接标准 (PCB Board Welding Standard)	
AWG	温升 60 $^{\circ}\text{C}$	温升 85 $^{\circ}\text{C}$	PCB 板 + 焊盘厚度 : 1.6-2.0mm	焊脚高度 3.0mm
8#	55A	60A		
10#	50A	55A		
12#	45A	50A		