

ME1T Series

1W, Unregulated, 1.5KV Isolation, SMD Package DC/DC Converters



Features

- Rated power: 1W max
- Input voltage range $\pm 10\%$
- Unregulated single output
- High efficiency up to 88%
- Isolation voltage 1.5KVDC
- Small no load input current
- Operating temperature range: $-40 \sim +105^{\circ}\text{C}$ ambient
- RoHS compliant
- Compact SMD package
- Continuous short circuit protection
- Designed to meet UL/EN/IEC 62368-1
- 3 year warranty



Overview

The ME1T series are unregulated DC/DC converters offered in compact SMD package with 1.5KVDC isolation. These converters feature high efficiency, low ripple and noise, continuous short circuit protection, and wide operating temperature range $-40 \sim +105^{\circ}\text{C}$. They are widely used in distributed power system in industrial applications where isolation and voltage converting is needed.

Model Numbers

Model Number	Input Voltage [VDC] $\pm 10\%$	Output Voltage [VDC]	Output Current [mA]		Efficiency [%] Typ.	Capacitive Load [μF] Max.
			Max.	Min.		
ME1T-0303	3.3	3.3	303	0	80	3000
ME1T-0305	3.3	5	200	0	82	3000
ME1T-0309	3.3	9	111	0	83	1200
ME1T-0312	3.3	12	84	0	84	820
ME1T-0315	3.3	15	67	0	84	680
ME1T-0324	3.3	24	42	0	84	330
ME1T-0503	5	3.3	303	0	82	3000
ME1T-0505	5	5	200	0	85	3000
ME1T-0509	5	9	111	0	86	1200
ME1T-0512	5	12	84	0	86	820
ME1T-0515	5	15	67	0	86	680
ME1T-0524	5	24	42	0	87	330
ME1T-1203	12	3.3	303	0	82	3000
ME1T-1205	12	5	200	0	85	3000
ME1T-1209	12	9	111	0	86	1200
ME1T-1212	12	12	84	0	86	820
ME1T-1215	12	15	67	0	86	680
ME1T-1224	12	24	42	0	88	330

ME1T Series

1W, Unregulated, 1.5KV Isolation, SMD Package DC/DC Converters




Model Numbers [continued]

Model Number	Input Voltage [VDC] $\pm 10\%$	Output Voltage [VDC]	Output Current [mA]		Efficiency [%] Typ.	Capacitive Load [uF] Max.
			Max.	Min.		
ME1T-1505	15	5	200	0	86	3000
ME1T-1512	15	12	84	0	87	820
ME1T-1515	15	15	67	0	88	680
ME1T-2403	24	3.3	303	0	82	3000
ME1T-2405	24	5	200	0	85	3000
ME1T-2409	24	9	111	0	86	1200
ME1T-2412	24	12	84	0	87	820
ME1T-2415	24	15	67	0	87	680
ME1T-2424	24	24	42	0	88	330

* Only typical models are listed. Other models may be available upon request.

* Operating with less than 10% of rated load will not cause permanent damage to the converters, but the performances data may not fall into the specifications, and reliable operating is not assured.



ME1T Series

1W, Unregulated, 1.5KV Isolation, SMD Package DC/DC Converters



Electrical Specifications

Unless otherwise indicated, specifications are measured at $T_A=25^{\circ}\text{C}$, nominal input voltage, full load after warm up.

Parameters	Conditions	Min.	Typ.	Max.	Unit	Note
Input current Full load	$V_{IN}=3.3\text{V}$ $V_{IN}=5\text{V}$ $V_{IN}=12\text{V}$ $V_{IN}=15\text{V}$ $V_{IN}=24\text{V}$	-	370 230 99 80 51	-	mA	
Input current No load		-	10	-	mA	
Reflected Ripple Current		-	15	-	mA	
Surge voltage 1 second max	$V_{IN}=3.3\text{V}$ $V_{IN}=5\text{V}$ $V_{IN}=12\text{V}$ $V_{IN}=15\text{V}$ $V_{IN}=24\text{V}$	-0.7 -0.7 -0.7 -0.7 -0.7	-	5 9 18 21 30	VDC	
Output voltage accuracy	All models	Refer to graphic in "Characteristic Curves" section				
Line regulation For V_{IN} change of $\pm 1\%$	$V_{OUT}=3.3\text{V}$ All others	-	-	± 1.5 ± 1.2	%	
Load regulation $I_{OUT}=10\%$ to 100% of $I_{OUT, rated}$	$V_{OUT}=3.3\text{V}$ $V_{OUT}=5\text{V}$ $V_{OUT}=9\text{V}$ $V_{OUT}=12\text{V}$ $V_{OUT}=15\text{V}$ $V_{OUT}=24\text{V}$	-	15 10 9 8 7 6	20 15 10 10 10 10	%	
Temperature coefficient	Full load	-	± 0.02	-	$\%/^{\circ}\text{C}$	
Output ripple and noise	20MHz bandwidth	-	60	120	mVp-p	
Output short circuit protection		Continuous, automatic recovery				
Input filter		Capacitor				
Hot plug		None				

* Operating with less than 10% of rated load will not cause permanent damage to the converters, but the performances data may not fall into the specifications, and reliable operating is not assured.

ME1T Series


1W, Unregulated, 1.5KV Isolation, SMD Package DC/DC Converters



General Specifications

Parameters	Conditions	Min.	Typ.	Max.	Unit	Note
Isolation voltage 1 minute, leakage current <1mA	Input to Output	1500	-	-	VDC	
Isolation resistance Tested at 500VDC	Input to Output	1000	-	-	M ohm	
Isolation capacitance 100KHz, 0.1V	Input to Output	-	20	-	pF	
Operating temperature	See "Derating Curve"	-40	-	+105	°C	
Storage temperature		-55	-	+125	°C	
Temperature rise at case	Full load	-	25	-	°C	
Storage humidity	Non-condensing	5	-	95	%RH	
Switching frequency	Full load	-	220	-	KHz	
Reflow soldering temperature		Peak temp. 217 - 245°C, maximum duration 60s				
Vibration		10-150Hz, 5G, 0.75mm along X, Y and Z				
Cooling method		Free air convection				
Design based on standards		IEC/EN/UL 62368-1				
Safety certifications		IEC/EN 62368-1				
EMC	Emissions Immunity	CISPR32, EN55032 Class B* IEC/EN61000-4-2, air ±8kV, contact ±4kV				
MTBF	MIL-HDBK-217F	>3,500,000 Hours, T _A =25°C				
Moisture sensitivity level [MSL]		IPC/JEDEC J-STD-020D.1 Level 1				
Size		13.5 x 11 x 7.25 mm				
Weight		1.6g Typ.				

*External circuit is required in order to meet Class B, refer to Figure 2 in Recommended External Circuit



ME1T Series


1W, Unregulated, 1.5KV Isolation, SMD Package DC/DC Converters



Characteristic Curves


Derating Curve

Output vs Ambient Temperature




Output Voltage Accuracy vs Load

None 3.3V output models



3.3V output models




Characteristic Curves [continued]

Efficiency Curves


Efficiency vs Input Voltage

ME1T-0305, with full Load




Efficiency vs Load

ME1T-0305, with nominal input voltage




Efficiency vs Input Voltage

ME1T-0505, with full Load




Efficiency vs Load

ME1T-0505, with nominal input voltage





Efficiency vs Input Voltage

ME1T-1205, with full Load



Efficiency vs Load

ME1T-1205, with nominal input voltage



Recommended External Circuit

Typical Application Circuit

*Typical application circuit is to further lower the input and output ripple. It is not required for general use.

*Recommended component specifications are typical values. Excessive external capacitive load may cause startup problem.




Figure 1. Typical external circuit

[Table 1] Recommended component spec

Input voltage	3.3, 5V	12V	15V	24V
C _{IN}	4.7uF, 16V	2.2uF, 25V	2.2uF, 25V	1uF, 50V

[Table 2] Recommended component spec

Output voltage	3.3, 5V	9V	12V	15V	24V
C _{OUT}	10uF, 16V	4.7uF, 16V	2.2uF, 25V	1uF, 25V	0.47uF, 50V

Circuit for EMC Enhancement

*Use this application circuit to meet Class B EMC performance.




Figure 2. Circuit for EMC enhancement

[Table 3] Recommended component spec


Component	LDM	C1, C2	CY	C3
C _{OUT}	6.8uH	4.7uF, 50V	270pF, 2KV	Refer to C _{OUT} in [Table 2]

ME1T Series

1W, Unregulated, 1.5KV Isolation, SMD Package DC/DC Converters



Mechanical Specifications



Pin Definition

Pin #	Single Out
1	GND
2	V _{IN}
4	0V
5	+V _{OUT}
8	No connection

* Unless otherwise specified unit: mm [inch]

* General tolerance: ± 0.50 [± 0.020]

* Pin thickness: ± 0.10 [± 0.004]

* Footprint grid 2.54 x 2.54 mm