

# DC/DC CONVERTERS

Isolated, Unregulated  
SIP / DIP Package

- Cost effective selections
- Industrial standard pinning
- Continuous short circuit protected
- Operating temperature up to +105°C

- 3 year warranty
- RoHS and REACH compliant
- Certified to UL/EN/IEC 62368-1
- Meet CISPR32, EN55032 Class B

UL Certified

CE - EN/IEC 62368-1

~40~+85°C Temp. Range

~40~+105°C Temp. Range

Continuous S.C.P.

IMAGE	SERIES	POWER [W]	INPUT VOLTAGE RANGE [VDC] ±10%	OUTPUT VOLTAGE [VDC]	ISOLATION [KVDC]	PACKAGE	SIZE [mm]	FEATURES				
	MEG1SA	1	12, 15, 24	3.3, 5, 9, 12, 15, 24 ±5, ±9, ±12, ±15	6.0	SIP	19.5x9.8x12.5	■	■	■	■	■
	MEG2SA	2	12, 15, 24	5, 9, 12, 15, 24 ±5, ±9, ±12, ±15	6.0	SIP	19.5x9.8x12.5	■	■	■	■	■
	ME1N	1	3.3, 5, 12, 15, 24	3.3, 5, 7.2, 9, 12, 15, 24	1.5	DIP	12.7x10.16x8.2	■	■	■	■	■
	MEK1N	1	5, 12, 15, 24	3.3, 5, 7.2, 9, 12, 15, 24	3.0	DIP	12.7x10.16x8.2	■	■	■	■	■
	ME1D	1	5, 12, 15, 24	±3.3, ±5, ±9, ±12, ±15, ±24	1.5	DIP	20.0x10.0x7.0	■	■	■	■	■
	MEK1D	1	5, 12, 15, 24	5, 12, 15 ±3.3, ±5, ±9, ±12, ±15	3.0	DIP	20.0x10.0x7.0	■	■	■	■	■
	ME2D	2	3.3, 5, 12, 15, 24	3.3, 5, 9, 12, 15, 24 ±3.3, ±5, ±7, ±9, ±12, ±15, ±24	1.5	DIP	20.32x10.16x8.2	■	■	■	■	■
	MEK2D	2	5, 12, 15, 24	3.3, 5, 9, 12, 15, 24 ±3.3, ±5, ±9, ±12, ±15, ±24	3.0	DIP	20.32x10.16x8.2	■	■	■	■	■