

DC/DC CONVERTERS

Isolated, Regulated,
2:1 / 4:1 Input Range, DIP24 Package

- Compact SIP / DIP package
- Wide input voltage range 2:1 or 4:1
- Optional remote On/Off and Trim function
- Optional heatsinks and chassis available

- 3 year warranty
- RoHS and REACH compliant
- Certified to UL/EN/IEC 62368-1
- Meet CISPR32, EN55032 Class B

UL Certified

CE - EN/IEC 62368-1

Remote On/Off Control

Output Trim / Sense

Optional Chassis

IMAGE	SERIES	POWER [W]	INPUT VOLTAGE RANGE [VDC]	OUTPUT VOLTAGE [VDC]	ISOLATION [KVDC]	PACKAGE	SIZE [mm]	FEATURES				
	MV3D	3	4.5~9, 9~18, 18~36, 36~75	3.3, 5, 9, 12, 15, 24 ±5, ±9, ±12, ±15	1.5	DIP24	32.0x20.0x10.8		■			
	MV6D	6	4.5~9, 9~18, 18~36, 36~75	3.3, 5, 12, 15, 24 ±5, ±9, ±12, ±15	1.5	DIP24	32.0x20.0x10.8		■			
	MV10D	10	9~18, 18~36, 36~75	5, 12, 15, 24 ±5, ±12, ±15	1.5	DIP24	32.0x20.0x10.8		■	■		
	MVK3P	3	4.5~9, 9~18, 18~36, 36~75	3.3, 5, 12, 15, 24 ±5, ±9, ±12, ±15	1.5	DIP24	31.6x20.3x10.2		■			
	MU3D	3	9~36, 18~75	3.3, 5, 9, 12, 15, 24	1.5	DIP24	32.0x20.0x10.8		■			
	MU6D	6	9~36, 18~75	3.3, 5, 9, 12, 15, 24 ±5, ±9, ±12, ±15	1.5	DIP24	32.0x20.0x10.8		■			
	MU10D	10	9~36, 18~75	3.3, 5, 12, 15, 24 ±5, ±12, ±15	1.5	DIP24	32.0x20.0x10.8		■	■		
	MUK3P	6	9~36, 18~75	3.3, 5, 9, 12, 15, 24 ±5, ±9, ±12, ±15, ±24	3.0	DIP24	32 x 20 x 121		■			
	MUK6P	6	9~36, 18~75	3.3, 5, 12, 15, 24 ±5, ±12, ±15	3.0	DIP24	31.6x20.3x10.2		■			
	MUR6P	6	9~36, 18~75	5, 6, 9, 12, 15, 18, 24	6.0	DIP24	31.6x20.3x10.2		■			