





The information provided herein is from CONNLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNLY or its affiliates. Unauthorized use of this information for any purpose other than the intended use is prohibited. CONNLY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.

Dept
Qty
DC 1
ED 1
IE 1
ISO 1
PD 1
R&D 1
SD 1
QA 1
QC 1
QE 1


A
B
C
D
E
F
G
H




(Series Image-Reference Only)

Dimension



Position	A±0.2	B±0.2	C±0.3	D	E
15	17.90	24.99	30.80	16.33	2.29
26	26.50	33.32	39.14	24.66	2.29
44	40.00	47.04	53.04	38.38	2.29
62	56.50	63.50	69.32	54.84	2.14
78	54.30	61.00	67.04	52.34	2.14



Standard type



CC type



CS type

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJH 09/26/05'	~	LJC 09/26/05'
B	整理图面	YCH 05/26/07'	~	LJC 05/26/07'
C	增加锁螺丝类型	YCH 06/30/07'	~	LJC 06/30/07'
D	DRAWING UPDATE	JLZ 08/08/18'	~	


NOTES:

- Electrical characteristics:
 - Contact resistance: 20mΩ Max. Initial.
 - Dielectric withstanding voltage: 500V AC(rms) for 1 minute.
 - Insulation resistance: 1000MΩ Min.
- Environment characteristics:

Temperature range: -40°C~+105°C.
- Materials:
 - Insulator: Thermoplastic.
 - Contact: Copper alloy.
 - Shell: Steel.
 - Screw: Copper alloy.

4. Product number code:

DS1035-







GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE	D-SUB H.D SOLDER TYPE	
X.	±0.60	X.	±5°	UNITS	mm		
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1035 SERIES
.XX	±0.25	.XX	±2°				
DRAWING TYPE		CUSTOMER					
SCALE		1:1	SHEET 1 OF 1				
DRAWING NO.		C-DS1035-XXXXXXX-D					








晨翔电子有限公司
CONNFLY CONNLY ELECTRONIC CO. LTD

Dept Qty
DC 1
ED 1
IE 1
ISO 1
PD 1
R&D 1
SD 1
QA 1
QC 1
QE 1

The information provided herein is from CONNLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNLY or its affiliates. Unauthorized use of this information for any purpose other than the intended purpose is strictly prohibited. CONNLY may enforce its intellectual property rights at its own discretion, failures or delays in exercise of such rights, does not constitute a waiver of such rights.



(Series Image-Reference Only)



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LL 12/06/06'	~	LJC 12/06/06'
B	增加锁螺丝类型	YCH 06/30/07'	~	LJC 06/30/07'
C	DRAWING UPDATE	JLZ 07/20/17'	HZW 07/20/17'	LJC 07/20/17'
D	DRAWING UPDATE	JLZ 08/08/18'	~	

NOTES:

- Electrical characteristics:
 - Contact resistance: 20mΩ Max. Initial.
 - Dielectric withstanding voltage: 500V AC(rms) for 1 minute.
 - Insulation resistance: 1000MΩ Min.
- Environment characteristics:

Temperature range: -40°C~+105°C.
- Materials:
 - Insulator: Thermoplastic.
 - Contact: Copper alloy.
 - Shell: Steel.
 - Screw: Copper alloy.

4. Product number code:

DS1035- X X X X X X

- Screw DIM. A
S: Standard(W/O nut)
1: 3.00
2: 4.00
3: 4.50
4: 5.00
5: 5.50
6: 5.80
- Screw type
S: Standard(W/O nut)
1: CC type
2: CS type
- Contact plating
8: Full gold flash
Si: Selective gold flash
- Shell plating
N: Fornt shell nickel,Back shell tin
- Housing color
B: Black
W: White
U: Blue
- Connector type
M: Male
F: Female
- No.of contacts
78: 78pos.

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE	D-SUB H.D SOLDER TYPE	
X.	±0.60	X.	±5°	UNITS	mm		
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1035 SERIES
.XX	±0.25	.XX	±2°				
DRAWING TYPE		CUSTOMER					
SCALE		1:1	SHEET 1 OF 1				
DRAWING NO.		C-DS1035-78XXXXXX-D					



晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD