

A	Dept	1	2	3	4	5	6	7	8	A						
	Qty	1														
	DC	1														
	ED	1														
	IE	1														
	ISO	1														
B	PD	1								B						
	R&D	1														
	SD	1														
	QA	1														
C	QC	1								C						
	QE	1														
D	The information provided herein is from CONNLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNLY or its affiliates. Unauthorized use or modification is strictly prohibited without prior written consent from CONNLY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNLY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.										D					
											E	CONNLY Tel:86-574-63508787 Fax:86-574-63510817 E-mail:sale@connfly.com http://www.connfly.com Add:East Industry Zone KuangYan Town Cixi Ningbo China P.C:315333				
F	Right Angle V/T Type										F					
G	Female Terminal Female Housing N=No. of contacts										G					
H	Female Terminal Female Housing N=No. of contacts										H					
						REV. DESCRIPTION DRAWN CHECKED APPROVED A NEW RELEASE HP 29/06/05 LJC 29/06/05 B ADD P/N CODE JLZ 01/30/15' LJC 01/30/15' C DRAWING UPDATE JLZ 12/27/16' D DRAWING UPDATE JLZ 07/18/18'					NOTES: 1. MAIN SPECIFICATIONS . Housing material: NYLON 66 . Wire range: AWG#22~#18 . Rated voltage: 250V . Rated current: 7A . Contact resistance: ≤30mΩ . Insulation resistance: ≥1000MΩ . Withstanding voltage: 1000V,AC 1 minute . Temperature range: -25 ~ +85°C . Recommend PC board thickness:1.6mm 2. PRODUCT NUMBER CODE: DS1073 - X X X X X Contact Plating 6: Tin 8: Full gold flash Housing Color W: White Mounting type R: Right Angle V: V/T type Connector type M: Male No.of contact 2 to 13					
						GENERAL TOLERANCE ANGLE TOLERANCE PROJECTION TITLE UNITS mm P.C.B CONNECTOR 3.96mm VH SHEET SIZE A4 SERIES DS1073 SERIES 晨翔电子有限公司 CONNLY CONNLY ELECTRONIC CO. LTD										
						DRAWING TYPE CUSTOMER SCALE 1:1 SHEET 1 OF 1 DRAWING NO. C-DS1073-XXXXX-D										