







未注公差/General tolerances(mm)														0.1/10 ±2'
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



3	Current Carrier	Copper	Sn plated
2	Shrapnel	Stainless steel	
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电流/Rated Voltage(V)/Current(A)		300/15	300/15
IEC 标准/IEC Standard:		D	
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	/
额定电压/电流/Rated Voltage(V)/Current(A)		800/24	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		8.0	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)		0.2~2.5/28~14	
间距/Pitch(mm)		10.0	
剥线长度/Stripping length(mm)		8-9	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	
标准颜色编号/Standard color number:			
PANTONE / RAL		/	

MATERIAL:		SURFACE:	
MAT NO.: /		 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS: /			
APPD: Li GL 2020.04.04			
CHKD: Mao J 2020.04.04			
DRFT: HXG 2008.10.04		NAME: WS2.5T-DB-01P-1Y-00A(H)	
DRAWING NO.: WS 2.5T-DB-C01		REV	TO
	SIZE: A4	 mm (inch)	TYPE: CUSTOMER DRAWING
SCALE: 2:1		SHEET	1/1

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

SIZE: A4	mm (inch)
----------	--------------