

C54 IGBT 塑壳插片吸收电容器

Main technical parameters


Rated capacitance	Cn	2.2uF
Capacitance tolerance		±10%
Dissipation Factor	tg δ	≤10 ⁻⁴ (25°C±5°C,1KHz)
Rated voltage	Un	1000V.DC
Insulation Resistance	IR	≥5 000S (25°C±5°C,500V,1min)
Maximum current	Irms	19A(70°C;100KHz)
Maximum peak current	Ip-p	1870A
Series resistance	ESR	4.0m Ω (100KHz)
Self inductance	Ls	≤29nH
Failure quota	λ	100Fit
Operating Temperature Range	°C	-40~+85°C
Expected lifetime		100 000H
Max.Altitude	Alt	2000m
Reference Standard		IEC61071/IEC60831

Test parameters


Between Terminals	Ut-t	1.5*Un 10S
Between Terminals and Case	Ut-c	2000+2Un(VAC)(10S) (Min3000VAC)

产品工艺

Film		Metalized polypropylene film
Case		Flame-retardant plastic case
Epoxy		Flame-retardant Epoxy-white
Terminal		silvered copper terminal



DiN C54
1000V.DC
D/C 2.2uF±10%
www.csdin.com

Customer	Platan				
TYPE	Dimensions (mm)				Part No.
	L	H	W		
C54225K1000V	42	45	30		C542252FJ8K3AD35B
Approval by	Checked by	Made by	CUSTOMER CONFIRM		 深圳市创仕鼎电子有限公司 Tel:0755-29948886 29948363 Fax: 29948916 Http://www.csdin.com E-Mail:sales@csdin.com Address: Tower 3, NanTai YunChuang Vally, Tangwei, Fenghuang St. , Guangming District, 518107, Shenzhen, China
Rao		Zhang			
DATE	2022/5/27		DATE		