


MA111L

| | | |
|---------------------------------------|------------------------|--|
| Connection Type | | with Solder Terminal |
| Print | | (On-Off) Marked |
| Product | | Toggle Switch |
| Contact | | 1NO |
| Current | I_e | 16 A (250V AC) |
| Usage Category | | AC15 |
| Mechanical Life | Min Qty | 100000 |
| Electrical Life | Min Qty | 10000 |
| Operating Frequency | On-Off/Hour | Mech.900 Elec.900 |
| Insulation Voltage | U_i | 300V |
| Impulse Withstand Voltage | U_{imp} | 2.5 kV |
| Dielectric Strength (Body-Contact) | | 2.500V AC |
| Dielectric Strength (Contact-Contact) | | 1.500V AC |
| Isolation Resistance | | 10 MΩ min. (500V DC) |
| Operating Temperature | | -25 / +80 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP20 |
| Contact Material | | AgNi |
| Cable Section | | Terminal 6,3*0,8 mm |
| Short Circuit Breaking Capacity | I_{cs} | 1 kA |
| Serial | | MA Series |
| Specifications | | Maximum product reliability with V0 material |
| | | Different badge options |
| Standards / Certificates | | TS EN 61058-1 |

