



MKS1TM-25	
Operational Frequency	50-60 Hz
Product	Motor Protection Switch
Current	I_e 25 A
Thermic Current Calibration Interval	20,0-25,0A
Usage Category	AC 3
Mechanical Life	Min Qty 100000
Electrical Life	Min Qty 100000
Operating Frequency	On-Off/Hour Mek. 360 Elk. 360
Insulation Voltage	U_i 690V AC
Impulse Withstand Voltage	U_{imp} 6 kV
Dielectric Strength (Contact-Contact)	1890V
Isolation Resistance	10 MΩ Min. (500 V DC)
Operating Temperature	-5 / +40 °C
Pollution Degree	3
Protection Degree	IP40
Cable Section	0,75-4 mm ²
Screw Torque	1,8 Nm
Short Circuit Breaking Capacity	I_{cs} 6 kA
Production Time	Adjustable overload release 13 ranges between 0.1-25 A; Short circuit release factor set at 12xI _e ; Short circuit switching capacity minimum 6 kA / 400 V
Serial Specifications	MKS Series Adjustable overload release 13 ranges between 0.1-25 A Short circuit release factor set at 12xI _e Short circuit switching capacity minimum 6 kA / 400 V
Standards / Certificates	TS EN 60947-4-1

CE

ERT



TSE

UK
PA