

RE1P11AC024

| | | |
|---------------------------------------|------------------------|---|
| Operational Voltage | | 24VAC |
| Product | | Industrial Relay |
| Contact | | 3 Contact |
| Current | I_e | 10 A (250V AC) |
| Usage Category | | AC 15 |
| Mechanical Life | Min Qty | 10000000 |
| Electrical Life | Min Qty | 100000 |
| Operating Frequency | On-Off/Hour | Mech. 18.000 Elec. 600 |
| Insulation Voltage | U_i | 300 V |
| Impulse Withstand Voltage | U_{imp} | 1,5kV |
| Dielectric Strength (Body-Contact) | | 2.500V AC |
| Dielectric Strength (Contact-Contact) | | 1.500V AC |
| Isolation Resistance | | MIN. 10 MΩ (500 V DC) |
| Operating Temperature | | -15 / +80 °C |
| Pollution Degree | | 3 |
| Protection Degree | | IP40 |
| Contact Material | | AgNi |
| Serial | | RE1 Series |
| Pin | | 11 Pin |
| Specifications | | PA6.6 base non-flammable body |
| | | 35 mm rail assembly with 8 and 11 pins socket |
| | | Test button and indicator |
| Standards / Certificates | | TS EN 61810-1 |

