

SCB22MP1PC1

Sensing Distance		Touch
Sensing Face		PBT
Connection Type		1m Cable
Operational Voltage		10-30V DC
Product		Capacitive Button
Type		Momentary
Mounting		Non Flush
Dia		22mm
Insulation Voltage	Ui	1500 VAC
Impulse Withstand Voltage	Uimp	75V DC
Operating Temperature		-25°C...+70°C
Pollution Degree		3
Protection Degree		IP67
Number of Contact		1
Repeat Accuracy		<0,1 Sr
Output/Contact Type		PNP-NO
Reverse Polarity Protection		Available
Short Circuit Protection		Available
Max. Load Current		200 mA hiccup
Temperature Drift		<0,1 Sr
Time Delay Before Availability		≤100 ms
No Load Current		< 15 mA
Leakage Current		≤0,5mA
Min. Load Current		< 1mA
Voltage Drop		< 2 V
Ripple (Voltage)		< %10
EMC		61000-4-3 3V/m -- 61000-4-6 3
Conditional Short Circuit Current		100A

Usage Category - Operating Current	DC13 - 200mA
Body Material	Plastic
Number of Cable and Cable Section	3 x 0,25 mm ²
Serial	SCB Series
Specifications	Rapid switching
	Easy to install to 22mm hole
	Short circuit and overload protection
	Reverse polarity protection
   	