



### SK5P

<b>Product</b>	Level Control Float Switch	
<b>Type</b>	Plastic Float	
<b>Phase Number</b>	1 Phase	
<b>Current</b>	<b>I<sub>e</sub></b>	3 A (240V AC)
<b>Usage Category</b>	AC15	
<b>Mechanical Life</b>	<b>Min Qty</b>	30000
<b>Electrical Life</b>	<b>Min Qty</b>	10000
<b>Operating Frequency</b>	<b>On-Off/Hour</b>	Mek.120 Elk.120
<b>Insulation Voltage</b>	<b>U<sub>i</sub></b>	300 V
<b>Impulse Withstand Voltage</b>	<b>U<sub>imp</sub></b>	2,5 kV
<b>Dielectric Strength (Body-Contact)</b>	2.500V AC	
<b>Dielectric Strength (Contact-Contact)</b>	1.500V AC	
<b>Isolation Resistance</b>	10 MΩ Min. (500 V DC)	
<b>Operating Temperature</b>	-15 / + 80 °C	
<b>Pollution Degree</b>	3	
<b>Protection Degree</b>	IP65	
<b>Contact Material</b>	AgNi	
<b>Cable Section</b>	1.5-2.5 mm <sup>2</sup>	
<b>Screw Torque</b>	1.5Nm	
<b>Serial</b>	SK5 Series	
<b>Specifications</b>	Easy assembly	
	Feature to adjust the requested operation interval with weight	
	Different cable length options	
	Waterproof	
<b>Standards / Certificates</b>	TS EN 60730-2-15	