

# **SR-6** - Sensor Socket for TGS24xx and 26xx-series Sensors

### Features:

- \* Durable for over 100 insertions and removals
- \* Firmly fixes sensor into place

## **Applications:**

- \* For use in preheating racks, test and calibration equipment
- \* For use in finished products

Top view




SR-6 is a reliable and durable socket supplied by Figaro, designed specifically for usage with TGS24xx and 26xx series sensors.

Side view

### **Structure and Dimensions**

## Specifications:

| Model No. | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | SR-6 | Applicable gas sensor | Figaro 24xx and 26 | SR-6 | S



Model No.		SR-6
Applicable gas sensor		Figaro 24xx and 26xx series
Operating conditions		-20°C ~ 70°C
Material	Contact pins	Berylium copper (gold plate finish)
	Sleeve	Brass or bronze (tin plate finish)
	Insulator	Polyphenylene sulfide (PPS)
Weight		approx 1.5g

**Bottom view** 

#### FIGARO ENGINEERING INC.

1-5-11 Senba-nishi Mino, Osaka 562 JAPAN Phone: (81)-72-728-2561 Fax: (81)-72-728-0467 email: figaro@figaro.co.jp