

PANEL CUT-OUT		
Z	X	Y
0.70~1.25	22.10~22.40	21.8~22.0
1.25~2.00	22.40~23.00	21.8~22.0
2.00~3.00	23.20~23.80	21.8~22.0

NOTES:

1. Rating:

- CQC 6A 250V AC 6(8)A 250V AC
- 8A/128A 250V AC T105/55
- UL CUL 10GPA 125V AC
- 6GPA 250V AC T105/55
- VDE ENEC 6(4)A 250V AC T85/55
- KC 6(4)A 250V AC T85/55

2. Circuit Diagram: 6P ON-ON

3. Terminal Strength: ≥80N

4. Electrical life: ≥10000 cycles

5. Withstand Voltage:


- Withstand Voltage: 1500VAC 1min
- Terminals to Button: 3000VAC 1min

6. Leakage Current: 1mA

7. Current resistance: ≤50mΩ (initial)

8. Insulation resistance: ≥100MΩ

9. Body Material: NYLON 66 94V-2~0



A4				普通公差:		温州港源电子有限公司 Wenzhou Gangyuan Electronics Co Ltd.							
A3				COMMON TOLERANCE :									
A2				UP TO 5	±0.20	单位	mm	投影		品名	跷板开关	比例	Free
A1				ABOVE 5 TO 30	±0.30	UNIT		PROJECTED		PRODUCT NAME		SCALE	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	±0.50	绘图	周金勇	核对	梁金勇	型号	RS601F2-2020011R3B		
				ANGULAR	±5°	DATE	2015.12.24	核准	周培雷	图号		