





REV	CONTENT	CHK	DATE
V0.0	CONTENT	SYJ	25.02.11

Electrical :
1.Rated Voltage :
2.Rated Current :
3.Wire Range:
4.Stripping Length : 10-12mm
5.Operating Temperature : -40°C~+105°C
6.RoHS Compliance
7."★" is the key quality control point



- ① Series NO.
② Wire diameter
③ Connection quantity
④ Color:
- GY-Grey
 - BU-Blue
 - BK-Black
 - GN-Green
 - OG-Orange
 - RD-Red
 - YE-Yellow
 - WH-White
 - PE-Yellow & Green
 - BE-Beige

A	Total Pitch Tolerances in mm									Nominal dimension range in mm									$\perp$		$\equiv$	$-$	$//$		
	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 250	over 350	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 10	all	over 0	over 100	over 150
	to 30	to 53	to 70	to 90	to 115	to 150	to 250	to 350	to 500	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10				to 100	to 150	
	± 0.18	± 0.20	± 0.25	± 0.3	± 0.35	± 0.44	± 0.60	± 0.70	± 0.85	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.3	0.2	0.3	0.5
6						5						4						6							

4	CONDUCTOR	XX	1	Copper alloy	Tin Plated			
3	BUTTON	XX	3	PBT	SEE NOTE			
2	SPRING	XX	3	Stainless Steel	/			
1	HOUSING	XX	1	PA66 UL94V-0	SEE NOTE			
ITEM	NAME OF PART		NO. OF PART	Q"TY	MATERIAL		NOTE	
DWG.	SYJ	DATE	25.02.11	SIZE	A4	UNITS	mm	SHEET/OF 1 / 1
CHK.		DATE		SCALE	1:1		GP4-3-X	
APP.		DATE			NAME			
Grolten 宁波冠泰电子有限公司				DWGNO.				
NINGBO GOLTEN ELECTRONICS CO., LTD.								