



- a. T568A & T568B wiring sticker.
- b. Insertion force : 30N max. (IEC 60603-7-5)
- c. Retention strength : 7.7 kg between Jack and Plug.
- d. Operating temperature : -10°C to 60°C.(ISO/IEC 11801, ANSI/TIA/EIA 568 B.2.)
- e. Life(mating cycles) :
 - *Jack : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-5)
 - *IDC : Suitable for 22-26 AWG stranded and solid wire, compatible with both 110 & Krone punch down tools.
- f. The Cat.5e transmission performance is in compliance with the ANSI/TIA/EIA 568 B.2 standard.

GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.005 X.XX ±0.05 X.X ±0.1	DRAWING	05.MAY.2011	YLL		 HOYUTEC International Co., Ltd.	ITEM NO.: HYC-K1813	DES.: CAT.5E FULL SHIELDED KEYSTONE JACK	 A6
	CHECK	05.MAY.2011	JANE					
	APPROVAL	05.MAY.2011	JAIMY					
		DATE	NAME					
	SCALE	1/1 (A4)	UNIT	mm				
		DRAWING NO.						
		DRAWING CLASSIFICATION		S	SHEET	1 OF 1		