


International  
**IOR** Rectifier

**203CNQ100PbF**

SCHOTTKY RECTIFIER

200 Amp



#### Major Ratings and Characteristics

| Characteristics                                    | Value      | Units            |
|--|------------|------------------|
| $I_{F(AV)}$ Rectangular waveform                   | 200        | A                |
| $V_{RRM}$  | 100        | V                |
| $I_{FSM}$ @tp = 5 $\mu$ s sine                     | 12,800     | A                |
| $V_F$ @100Apk, $T_J = 125^\circ\text{C}$ (per leg) | 0.70       | V                |
| $T_J$ range  | -55 to 175 | $^\circ\text{C}$ |

#### Description/ Features

The 203CNQ... center tap Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175  $^\circ\text{C}$  junction temperature. Typical applications are in high current switching power supplies, plating power supplies, UPS systems, converters, free-wheeling diodes, welding, and reverse battery protection.

- 175  $^\circ\text{C}$   $T_J$  operation
- Center tap module
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead-Free

#### Case Styles



TO-244

### Voltage Ratings

|  |              |
|--|--------------|
| Part number  | 203CNQ100PbF |
| V <sub>R</sub> Max. DC Reverse Voltage (V)             | 100          |
| V <sub>RWM</sub> Max. Working Peak Reverse Voltage (V) |              |

### Absolute Maximum Ratings

| Parameters   | 203CNQ | Units | Conditions  |
|--|--------|-------|---|
| I <sub>F(AV)</sub> Max. Average Forward Current (Per Leg) * See Fig. 5 (Per Device)      | 100    | A     | 50% duty cycle @ T <sub>C</sub> = 142 °C, rectangular wave form   |
|  | 200    |       |   |
| I <sub>FSM</sub> Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7 | 12,800 | A     | 5µs Sine or 3µs Rect. pulse<br>10ms Sine or 6ms Rect. pulse<br>Following any rated load condition and with rated V <sub>RRM</sub> applied |
|  | 1,700  |       |   |
| E <sub>AS</sub> Non-Repetitive Avalanche Energy (Per Leg)                                | 15     | mJ    | T <sub>J</sub> = 25 °C, I <sub>AS</sub> = 13 Amps, L = 0.2 mH   |
| I <sub>AR</sub> Repetitive Avalanche Current (Per Leg)                                   | 1      | A     | Current decaying linearly to zero in 1 µsec<br>Frequency limited by T <sub>J</sub> max. V <sub>A</sub> = 1.5 x V <sub>R</sub> typical     |

### Electrical Specifications

| Parameters  | 203CNQ | Units | Conditions  |
|---|--------|-------|---|
| V <sub>FM</sub> Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)    | 0.86   | V     | @ 100A<br>T <sub>J</sub> = 25 °C  |
|   | 1.03   | V     | @ 200A  |
|   | 0.70   | V     | @ 100A<br>T <sub>J</sub> = 125 °C   |
|   | 0.84   | V     | @ 200A  |
| I <sub>RM</sub> Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1) | 3      | mA    | T <sub>J</sub> = 25 °C  |
|   | 40     | mA    | T <sub>J</sub> = 125 °C<br>V <sub>R</sub> = rated V <sub>R</sub>          |
| V <sub>F(TO)</sub> Threshold Voltage                                    | 0.50   | V     | T <sub>J</sub> = T <sub>J</sub> max.                                      |
| r <sub>t</sub> Forward Slope Resistance                                 | 1.08   | mΩ    |   |
| C <sub>T</sub> Max. Junction Capacitance (Per Leg)                      | 2,650  | pF    | V <sub>R</sub> = 5V <sub>DC</sub> (test signal range 100Khz to 1Mhz) 25°C |
| L <sub>S</sub> Typical Series Inductance (Per Leg)                      | 7.0    | nH    | From top of terminal hole to mounting plane                               |
| dv/dt Max. Voltage Rate of Change (Rated V <sub>R</sub> )               | 10000  | V/ µs |   |

(1) Pulse Width < 300µs, Duty Cycle <2%

### Thermal-Mechanical Specifications

| Parameters   | Min        | Typ      | Max      | Units  |
|--|------------|----------|----------|--------|
| T <sub>J</sub> Max. Junction Temperature Range         | - 55       | -        | 175      | °C     |
| T <sub>Stg</sub> Max. Storage Temperature Range        | - 55       | -        | 175      |        |
| R <sub>thJC</sub> Thermal Resistance, Junction to Case | Per Leg    | -        | 0.38     | °C/W   |
|  | Per Module | -        | 0.19     | K/W    |
| R <sub>thCS</sub> Thermal Resistance, Case to Heatsink | -          | 0.10     | -        |        |
| Wt Weight  | -          | 68 (2.4) | -        | g (oz) |
| Mounting Torque  | 35.4 (4)   | -        | 53.1 (6) | lbf*in |
| Mounting Torque Center Hole                            | 30 (3.4)   | -        | 40 (4.6) | (Nm)   |
| Terminal Torque  | 30 (3.4)   | -        | 44.2 (5) |        |
| Vertical Pull  | -          | -        | 80       | lbf.in |
| 2 inch Lever Pull                                      | -          | -        | 35       |        |




Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance  $Z_{thJC}$  Characteristics (Per Leg)




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Max. Non-Repetitive Surge Current (Per Leg)






Fig. 8 - Unclamped Inductive Test Circuit

- (2) Formula used:  $T_c = T_j - (P_d + P_{d_{REV}}) \times R_{thJC}$ ;  
 $P_d = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)}/D)$  (see Fig. 6);  
 $P_{d_{REV}} = \text{Inverse Power Loss} = V_{R1} \times I_{R1} (1-D)$ ;  $I_{R1} @ V_{R1} = 80\%$  rated  $V_R$

Outline Table



Ordering Information Table



203CNQ100PbF

Bulletin PD-21103 12/05

International  
**IR** Rectifier

---

Data and specifications subject to change without notice.  
This product has been designed and qualified for Industrial Level and Lead-Free.  
Qualification Standards can be found on IR's Web site.

International  
**IR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7309  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 12/05