

## 120X120X25 mm

## JF1225-02 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** :  $\pm 10\%$

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF1225-1UR02	B, H	12	10.2 ~ 13.8	100.50	0.269	3000	0.50	6.00	0.50	45.7	195
JF1225-1SR02	B, H			89.87	0.224	2700	0.37	4.44	0.37	42.8	
JF1225-1H-02	B, H, S			80.11	0.186	2400	0.25	3.00	0.30	39.5	
JF1225-1M-02	B, H, S			69.57	0.147	2100	0.20	2.40	0.25	36.3	
JF1225-1L-02	B, H, S			59.57	0.111	1800	0.14	1.68	0.20	32.4	
JF1225-1E-02	B, H, S			47.88	0.078	1500	0.10	1.20	0.12	27.4	
JF1225-2UR02	B, H	24	20.4 ~ 27.6	100.50	0.269	3000	0.28	6.72	0.28	45.7	
JF1225-2SR02	B, H			89.87	0.224	2700	0.21	5.04	0.21	42.8	
JF1225-2H-02	B, H, S			80.11	0.186	2400	0.20	4.80	0.25	39.5	
JF1225-2M-02	B, H, S			69.57	0.147	2100	0.14	3.36	0.20	36.3	
JF1225-2L-02	B, H, S			59.57	0.111	1800	0.11	2.64	0.15	32.4	
JF1225-2E-02	B, H, S			47.88	0.078	1500	0.08	1.92	0.10	27.4	
JF1225B4UR02	Dual Ball	48	40.8 ~ 60.0	100.50	0.269	3000	0.14	6.72	0.14	45.7	
JF1225B4SR02				89.87	0.224	2700	0.12	5.76	0.12	42.8	
JF1225B4HR02				80.11	0.186	2400	0.10	4.80	0.10	39.5	
JF1225B4MR02				69.57	0.147	2100	0.08	3.84	0.08	36.3	
JF1225B4LR02				59.57	0.111	1800	0.07	3.36	0.07	32.4	
JF1225B4ER02				47.88	0.078	1500	0.06	2.88	0.06	27.4	

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

