

DC AXIAL FAN

JAMICON®

80X80X25 mm

KF0825-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS													
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)		
KF0825B1TR	Dual Ball	12	10.2 ~ 13.8	57.28	0.38	4500	0.42	5.04	0.50	42.10	86		
KF0825B1UR				50.25	0.30	4000	0.29	3.48	0.35	39.00			
KF0825B1SR				43.97	0.23	3500	0.25	3.00	0.30	34.80			
KF0825-1H	B, H, S			37.40	0.17	3000	0.17	2.04	0.20	30.90			
KF0825-1M	B, H, S			30.60	0.12	2500	0.10	1.20	0.12	25.80			
KF0825-1L	B, H, S			24.20	0.08	2000	0.07	0.84	0.08	22.30			
KF0825-1E	B, H, S			18.44	0.05	1500	0.04	0.48	0.05	20.50			
KF0825B2UR	Dual Ball			24	20.4 ~ 27.6	50.25	0.30	4000	0.17	4.08		0.20	39.00
KF0825B2SR						43.97	0.23	3500	0.15	3.60		0.18	34.80
KF0825-2H		B, H, S	37.40			0.17	3000	0.11	2.64	0.13		30.90	
KF0825-2M	B, H, S	30.60	0.12			2500	0.08	1.92	0.10	25.80			
KF0825-2L	B, H, S	24.20	0.08			2000	0.06	1.44	0.07	22.30			
KF0825-2E	B, H, S	18.44	0.05			1500	0.04	0.96	0.05	20.50			
KF0825B4UR	Dual Ball	48	40.8 ~ 60.0			50.25	0.30	4000	0.13	6.24		0.16	39.00
KF0825B4SR						43.97	0.23	3500	0.10	4.80		0.12	34.80
KF0825B4HR						37.40	0.17	3000	0.07	3.36		0.08	30.90
KF0825B4MR				30.60	0.12	2500	0.05	2.40	0.06	25.80			
KF0825B4LR				24.20	0.08	2000	0.03	1.44	0.04	22.30			

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

