



Klemsan®

MSB – Glass Cartridge Fuses

Application: protection of electronic and semiconductor equipment.

General Product Information

Rated current / opening time					
2,1 x I _n		2,75 x I _n		4 x I _n	
max.	min.	max.	min.	max.	max.
5x20 F: 100mA - 6,3A					
30min	50ms	2s	10ms	300ms	20ms
5x20 F: 6,3A - 10A					
30min	50ms	2s	10ms	400ms	40ms

Size	5 x 20
Type	Glass / Fast Blow (F)
Rated voltage	250 V AC
Packing unit	25 pcs.



Ordering number	Rated current	Breaking capacity	Max dV	Description
359003	1 A	35 A	200 mV	Cartridge fuse for fuse terminal - 1 A (5x20)
359004	2 A	35 A	170 mV	Cartridge fuse for fuse terminal - 2 A (5x20)
359007	4 A	35 A	130 mV	Cartridge fuse for fuse terminal - 4 A (5x20)
359008	6,3 A	63 A	130 mV	Cartridge fuse for fuse terminal - 6,3 A (5x20)
359010	250 mA	35 A	1400 mV	Cartridge fuse for fuse terminal - 250 mA (5x20)
359011	5 A	35 A	130 mV	Cartridge fuse for fuse terminal - 5 A (5x20)
359005	2,5 A	35 A	170 mV	Cartridge fuse for fuse terminal - 2,5 A (5x20)
359006	3,15 A	35 A	150 mV	Cartridge fuse for fuse terminal - 3,15 A (5x20)
359009	10 A	63 A	120 mV	Cartridge fuse for fuse terminal - 10 A (5x20)
359013	315 mA	35 A	1300 mV	Cartridge fuse for fuse terminal - 315 mA (5x20)
359014	50 mA	35 A	3500 mV	Cartridge fuse for fuse terminal - 50 mA (5x20)
359015	0.5 A	35 A	1000 mV	Cartridge fuse for fuse terminal - 0,5 A (5x20)