



Material:
Terminal: Phos Bronze,
Tin plating, 15000PCB/Roll

- Electrical Characteristics:**
1. Poles: 2 to 30P
 2. Current rating: 1.0A
 3. Voltage rating: 50V
 4. Temperature range: -25°C to +85°C
 5. Contact resistance: $\leq 20m\Omega$
 6. Insulation resistance: $\geq 100M\Omega$
 7. Withstand voltage: 500V AC/minute
 8. Applicable wire: AWG #32 to #28

Order Information
L-KLS1-XF1-1.00-T-X

- Packing: R=Reel, T=Tubes
- T=Terminal
- Pitch: 1.00=1.00mm
- Series No.
- Type
- RoHS

| GENERAL TOLERANCE | PROJECTION | | Description: |
|------------------------|------------|------------|--|
| X. ± 0.50 | UNITS | mm | 1.00mm ZH Type Wire To Board Connector |
| .X ± 0.25 | SCALE | 1:1 | |
| .XX ± 0.10 | Draw by: | Jenny | |
| ANGLE TOLERANCE | Check by: | | KLS P/N: L-KLS1-XF1-1.00-T |
| X. $\pm 5^\circ$ | Date | 2018-03-01 | NingBo KLS ELECTRONIC CO.,L TD. |
| .X $\pm 3^\circ$ | SHEET | 1 OF 1 | |
| .XX $\pm 2^\circ$ | | | |