

Switch

Rocker Switch Series

KLS7-013 Rocker Switch Series




MATERIAL

1. Housing: Nylon 66
2. Rocker: PC & PA66
3. Contacts: Silver Alloy
4. Terminal: Brass Silver Plated
5. Lamp: Neon Lamp, Tungsten Lamp
6. Spring: SWP, SUS
7. Movable Arm: Brass Silver Plated



ELECTRICAL

1. Electrical Rating: 6(4)A 250VAC / 10A 125V0AC
2. Mechanical life: Over 30000 Cycles
3. Electrical life: Over 10000 Cycles
4. Contact Resistance: $\leq 50\text{m}\Omega$
5. Insulation Resistance: $\geq 100\text{M}\Omega$
6. High Voltage Resistance: $>1500\text{V}$ 1 min
7. Ambient Temperature: Terminal Side $-20^{\circ}\text{C} \sim +85^{\circ}\text{C}$;
Actuating Side $-20^{\circ}\text{C} \sim +55^{\circ}\text{C}$
8. Storage Temperature: $-30^{\circ}\text{C} \sim +80^{\circ}\text{C}$ Max
9. Atmospheric Humidity: Max 85%
10. Actuating force: 4~8N (depends on different switch function)
11. Flammability: UL94 V-2
12. Temperature rise at the terminal: Max 30°C (UI1054)
13. Solder ability of terminal: Max 350°C 3S



SWITCHING CIRCUIT	
ON-OFF	
ON-ON	

ORDER INFORMATION

