


0809 KSS Screw On Wire Connector



- Material: Tough thermoplastic, UL 94V-2 flame-retardant shell.
- Two wing makes move easy twist on termination of wires.
- Strip wires before application.
- Rated at 600 volt max. for building wiring.
- Temperature: 105°C (221° F)
- Spring design provided more secure connection.



Unit: mm								
	Item No.	B	C	E	Wires Combination		Color	Packing
					sq	AWG		
	<input type="checkbox"/> SW-Y11H	9.8	18.2	25.8	Max. 3#3.5 Min. 2#0.5	Max. 3#12 Min. 2#18	Yellow	100 pcs / Bag
NEW	<input type="checkbox"/> SW-Y12PH	11.2	18.3	29.0	Max. 4#3.5 Min. 3#0.5	Max. 4#12 Min. 3#26	Brown	
	<input type="checkbox"/> SW-Y12H	13.0	23.0	31.8	Max. 5#3.5 Min. 3#1.25	Max. 5#12 Min. 3#16	Red	
	<input type="checkbox"/> SW-Y13H	14.9	25.5	33.3	Max. 3#5.5 Min. 3#3.5	Max. 3#10 Min. 3#12	Grey	
	<input type="checkbox"/> SW-Y14H	17.8	31.8	40.0	Max. 3#8 Min. 2#5.5	Max. 3#8 Min. 2#10	Blue	

[Input Sample Order](#)

[Check Selected](#)

[Return All Selected](#)