

## PKGS-00LDP1-R












# Appearance & Shape







## **Applications**

Other Usage

For consumer use



## **Packaging Information**


Packaging	Specifications	Minimum Order Quantity
R	180mm Embossed Tape	2000

1 of 3





# PKGS-00LDP1-R




Operating Temperature Range	-40℃ to 85℃	
Primary Axis Inclined Angle	0°	
Sensitivity(typ.)	0.84pC/G	
Capacitance(typ.)	770pF	
Insulation Resistance(min.)	500ΜΩ	
Non-linearity(typ.)	1%	
Shock Resistance	1500G (0.5ms duration)	
Sensitivity Type	Electric charge sensitivity type	
Resonance Frequency	20kHz	
Storage Temperature Range	-40°C to 85°C	






# PKGS-00LDP1-R







Freq. Characteristics

Primary axis inclined angle

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL: http://www.murata.com/

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

PKGS-00LDP1-R