


METAL OXIDE VARISTOR

压敏电阻器

DIMENSIONS

外型尺寸


MYE30
Terminal A Type



MYE30
Terminal B Type



MYE30
Terminal C Type



ELECTRICAL CHARACTERISTICS 电性能参数

ITEM NO. 产品型号	SPECIFICATION (25°C) 规格						MAXIMUM RATING (85°C) 最大额定值				CERTIFICATION 安规认证		
	Varistor Voltage (1mA DC) 压敏电压			@I _p Clamping Voltage 在 I _p 下限制电压 (8/20μs)			Continuous Voltage 连续电压		Energy 能量 10/1000μs W _{TM} (J)	Peak Current 峰值电流 (8/20μs) I _{TM} (KA)	CE	UL	RoHS
	Min (V)	V _{NDCl} (V)	Max (V)	V _c (V)	I _p (A)	F=1KHz (pF)	V _{RMS} (V)	V _{DC} (V)					
MYE30-201□	184	200	224	340	200	4100	130	175	210	30	★		◆
MYE30-221□	198	220	242	360		3700	140	180	225		★		◆
MYE30-241□	216	240	259	395		3400	150	200	240		★		◆
MYE30-271□	255	270	300	455		2900	180	230	250		★		◆
MYE30-331□	297	330	363	550		2600	210	270	270		★		◆
MYE30-361□	326	360	396	595		2300	230	300	300		★		◆
MYE30-391□	354	390	429	650		2100	250	330	330		★		◆
MYE30-431□	389	430	466	710		2000	275	360	360		★		◆
MYE30-471□	425	470	517	790		1700	300	390	380		★		◆
MYE30-511□	462	510	552	840		1600	320	420	430		★		◆
MYE30-561□	522	560	625	950		1400	360	470	490		★		◆
MYE30-621□	558	620	674	1025		1300	390	505	550		★		◆
MYE30-681□	612	680	736	1120		1300	420	560	600		★		◆
MYE30-751□	675	750	815	1240		1100	460	615	520		★		◆
MYE30-781□	702	780	858	1300		1100	480	640	550		★		◆
MYE30-821□	738	820	900	1350		1000	510	675	580		★		◆
MYE30-911□	819	910	933	1400		950	550	700	620		★		◆
MYE30-951□	855	950	1000	1500		900	580	735	650		★		◆
MYE30-102□	900	1000	1080	1650		840	620	800	680		★		◆
MYE30-112□	990	1100	1180	1800		770	680	860	760		★		◆
MYE30-122□	1080	1200	1320	2000	690	750	970	800	★		◆		

MYE HIGH DUTY SERIES