

PANEL CUT-OUT		
Z	Y	X
0.70~1.25	12.90~13.10	18.9~19.1
1.25~2.00	12.90~13.10	19.1~19.2
2.00~3.00	12.90~13.10	19.3~19.4

NOTES:

1. Rating:

- CQC 6A 250VAC 6(8)A 250VAC
- 8A/128A 250VAC T105/55
- UL CUL 10GPA 125VAC
- 6GPA 250VAC T105/55
- VDE ENEC 6(4)A 250VAC T85/55
- KC 6(4)A 250VAC T85/55

2. Circuit Diagram: 2P ON-OFF

3. Terminal Strength: $\geq 80N$

4. Electrical life: ≥ 10000 cycles


5. Withstand Voltage: Withstand Voltage: 1500VAC 1min
Terminals to Button: 3000VAC 1min

6. Leakage Current: 1mA

7. Current resistance: $\leq 50m\Omega$ (initial)

8. Insulation resistance: $\geq 100M\Omega$

9. Body Material: NYLON 66 94V-2~0



A4				普通公差:									
A3				COMMON TOLERANCE:									
A2				UP TO 5	±0.20	单位	mm	投影		品名	跷板开关	比例	Free
A1				ABOVE 5 TO 30	±0.30	UNIT		PROJECTED		PRODUCT NAME			
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	±0.50	绘图	周金勇	核对	梁金勇	型号	RS601		
				ANGULAR	±5°	DRAWN BY		CHECKED BY		MODEL NO.			
						日期	2015.10.15	核准	周培雷	图号	RS601A-1010011BB		
						DATE		APPROVAL BY		DWG NO.			