



RUTASEAL LIGHT® EPDM Metric



Material

EPDM - Halogen Free
Resistant to chemicals and weatherproof.

Suitable for holes in materials of 1 - 4 mm thickness.
Quick and simple assembly without the use of tools.

Mode of protection

IP67 acc. to EN 60529

Temperature range


-40°C...+110°C ⁽¹⁾


Test standard

SEMKO 44:1984

Semko report

300965



E-number	Size	For cable/ pipe Ø mm	A mm	B mm	Da mm	H mm	H1 mm	Pcs pack	
RAL 7001									
T_14 583 26	M16	5 - 9	16,5	1 - 4	21	17,5	11	50	2000
T_14 583 27	M20	8 - 12	20,5	1 - 4	25,5	19,6	13,4	50	3000
T_14 583 28	M25	11 - 16	25,5	1 - 4	30,5	20,9	15,3	50	2000
RAL 9005									
T_14 583 30	M16	5 - 9	16,5	1 - 4	21	17,5	11	50	2000
T_14 583 31	M20	8 - 12	20,5	1 - 4	25,5	19,6	13,4	50	3000
T_14 583 32	M25	11 - 16	25,5	1 - 4	30,5	20,9	15,3	50	2000
RAL 7035									
T_14 583 34	M16	5 - 9	16,5	1 - 4	21	17,5	11	50	2000
T_14 583 35	M20	8 - 12	20,5	1 - 4	25,5	19,6	13,4	50	3000
T_14 583 36	M25	11 - 16	25,5	1 - 4	30,5	20,9	15,3	50	2000



RUTASEAL®



**RUTASEAL
LIGHT®**

RUTASEAL LIGHT® was originally designed for strip lighting manufacturers and similar applications. Less material makes it lighter and easier to install, while providing IP67 protection. At the same time it is also easier to pull it out of the opening.

(1) Unstressed material.