

Surface Mount Type

Discontinued


Series: EN

■ Features

- Re-flow soldering method available (250 ° C)
- Miniaturized: Longer life and environmentally friendly
- RoHS directive compliant

■ Recommended Applications

- Memory cards(power supply to hold memory), mobile phones, PDAs, digital cameras.



■ Specifications

| | | |
|------------------------------------|--|--|
| Category Temp. Range | -10 °C to +60 °C | |
| Maximum Operating Voltage | 3.3 V.DC | |
| Nominal Capacitance | 0.2 F | |
| Maximum Operating Current | 10 μA max. | |
| Characteristics at Low Temperature | Capacitance change | ±30 % of initial measured value at +20 ° C(at -10 ° C) |
| | Internal resistance | <10 times of initial measured value at +20 ° C(at -10 ° C) |
| Endurance | After 500 hours application of 3.3 V.DC at +60 ° C, the capacitor shall meet the following limits. | |
| | Capacitance change | ±30 % of initial measured value |
| | Internal resistance | 4 kΩ or less |
| Shelf Life | After 500 hours storage at +60 ° C without load, the capacitor shall meet the following limits. | |
| | Capacitance change | ±30 % of initial measured value |
| | Internal resistance | 1 k ohm or less |

■ Dimensions in mm(not to scale)

(Unit : mm)

| Type AK | Type RK | Type J2 |
|---------|---------|---------|
| | | |

■ Standard Products

| Maximum Operating Voltage (V.DC) | Capacitance (F) | Capacitance tolerance (F) | Internal resistance (Initial specified value) (Ω) at 1kHz | Mass (g) | Part number | Min. Packaging Q'ty Reel (pcs) |
|----------------------------------|-----------------|---------------------------|---|----------|---------------|--------------------------------|
| 3.3 | 0.2 | 0.16 to 0.36 | < 200 | 0.2 | EECEN0F204() | 2000 |

The re-flow condition / taping dimensions are explained on EE210, EE211 of our Catalog. Please use it as a reference guide.

() : Please use AK, RK or J2 to indicate terminal type.

- Note : 1. When the capacitor is being used in a high temperature and high humidity environment for a long period, brown deposited materials might be found around the sealing area. However, the materials are insulators and will not affect any electrical characteristics of the capacitor.
2. Do not use reflow soldering when cell voltage is above 0.3 V.

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use. Should a safety concern arise regarding this product, please be sure to contact us immediately.

00 Sep. 2010