

2-IN-1 REWORK STATION

QUICK / 713

QUICK / 712



Features

- Password lock function, with auto sleeping/shutoff function.
- Digital temperature calibration, easy operation.
- Suction pen inside hot air handle, convenient for using.
- Brushless fan, adjustable, stepless and wide range of air volume, suitable for various occasions.
- Built-in vacuum pump, powerful suction, no need of external vacuum system.

Specifications

Soldering section	QUICK713	QUICK712
Power	90W	90W
Temperature range	200- 480℃	50- 500℃
Sleeping temperature range	200 ℃	50 ℃ -200 ℃
Sleeping time range	0- 99 min	0- 250 min
Temperature stability	±2 ℃ (Stationary air, no load)	±2 ℃ (Stationary air, no load)
Ambient temperature(Max)	40 ℃	40 ℃
Tip to ground resistance	< 2Ω	< 2Ω
Weight	About 7.9kg	About 4.8 Kg

Rework section		Specifications	
Power		1000W	
Temperature range		100- 500 ℃	
Air volume		1-120 Class	
Ambient temperature(Max)		40 ℃	
Temperature stability		± 2 ℃	

(Only for QUICK713)	
Desoldering section	Specifications
Heating power	90W
Temperature range	200 – 480 ℃
Pump	Diaphragm type
Vacuum pressure	600 mmHg
Sleep time range	1-100 min