


DATA INTERFACE

- OPERATING POWER SUPPLY VOLTAGE RANGE $4.8V \leq V_s \leq 36V$ (40V FOR TRANSIENTS)
- REVERSE SUPPLY (BATTERY) PROTECTED DOWN TO $V_s \geq -24V$
- STANDBY MODE WITH VERY LOW CURRENT CONSUMPTION $I_{S_{SB}} \leq 1\mu A$ @ $V_{CC} \leq 0.5V$
- MIN POSSIBLE BAUD RATE ACCORDING TO ISO9141 $\geq 130KBAUD$
- TTL COMPATIBLE TX INPUT
- BIDIRECTIONAL K-I/O PIN WITH SUPPLY VOLTAGE DEPENDENT INPUT THRESHOLD
- OVERTEMPERATURE SHUT DOWN FUNCTION SELECTIVE TO K-I/O PIN
- WIDE INPUT AND OUTPUT VOLTAGE RANGE $-24V \leq V_K \leq V_S$
- K OUTPUT CURRENT LIMITATION, TYP $I_K = 60mA$
- DEFINED OFF OUTPUT STATUS IN UNDER-VOLTAGE CONDITION AND V_S OR GND INTERRUPTION
- CONTROLLED OUTPUT SLOPE FOR LOW EMI
- HIGH INPUT IMPEDANCE FOR OPEN V_S OR GND CONNECTION




- DEFINED OUTPUT ON STATUS OF LO OR RX FOR OPEN LI OR K INPUTS
- DEFINED K OUTPUT OFF FOR TX INPUT OPEN
- INTEGRATED PULL UP RESISTORS FOR TX, RX AND LO
- EMI ROBUSTNESS OPTIMIZED

DESCRIPTION

The L9613B is a monolithic integrated circuit containing medium speed data interface functions.

BLOCK DIAGRAM




ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|-------------------------|--------------------------|------------------------|------|
| V _S | Supply Voltage | -24 to +36 | V |
| | ISO transient t ≤ 400ms | -24 to +40 | V |
| V _{CC} | Stabilized Voltage | -24V to 7 | V |
| dV _S /dt | Supply Voltage Transient | -10 to +10 | V/μs |
| V _{LI,K} | Pin voltage | -24 to V _S | V |
| V _{LO, RX, TX} | Pin voltage | -24 to V _{CC} | V |

* max ESD voltages are +/-2KV with human body model C=100pF, R=1.5KΩ corresponds to maximum energy

PIN CONNECTION



THERMAL DATA

| Symbol | Parameter | Min. | Typ. | Max. | Unit |
|----------------------|---|------|------|------|------|
| T _{JSDon} | Temperature shutdown switch-on-threshold | 160 | | 200 | °C |
| T _{JSDoff} | Temperature shutdown switch-off-threshold | 150 | | | °C |
| R _{th(j-a)} | Thermal steady state junction to ambient resistance | 130 | 155 | 180 | °C/W |

PIN FUNCTIONS

| N. | Name | Description |
|----|------|---------------------------|
| 1 | RX | Output for K as input |
| 2 | LO | Output L comparator |
| 3 | VCC | Stabilized voltage supply |
| 4 | TX | Input for K as output |
| 5 | GND | Common GND |
| 6 | K | Bidirectional I/O |
| 7 | VS | Supply voltage |
| 8 | LI | Input L comparator |

ELECTRICAL CHARACTERISTICS (The electrical characteristics are valid within the below defined Operating Conditions, unless otherwise specified).

The function is guaranteed by design until T_{JSDon} temperature shutdown switch-on-threshold.

V_S Supply voltage 4.8 V... 18 V

V_{CC} Stabilized voltage 3 V... 7 V

T_J Junction temperature -40 °C... 150°C

| Symbol | Parameter | Test Condition | Min. | Typ. | Max. | Unit |
|-------------------------------|------------------------------|---|-------------|--------|--------|------------|
| I_{CC} | Supply V_{CC} Current | $V_{CC} \leq 5.5V$ $V_{LI}, V_{TX} = 0V$ | | 1.4 | 2.5 | mA |
| | | $V_K \geq V_{K_{high}}$ $V_{LI} \geq V_{LI_{high}}$ $V_{TX} = V_{CC}$ @ $V_{CC} \leq 5.5V$ | -5 | 40 | 150 | μA |
| I_{SON} | Supply V_S Current | $V_{LI}, V_{TX} = 0V$ | | 3.5 | 10 | mA |
| | | $V_{CC} = 0.5V$ @ $V_S \leq 12V$ 3) | | <1 | 50 | μA |
| I_{SB} | | $V_{CC} = 0.5V$, see fig. 5 @ $V_S \leq 16V$ | | | 100 | μA |
| $V_{K_{low}}$ | Input Voltage LOW State | RX output status LOW | -24 | | 0.40VS | V |
| $V_{K_{high}}$ | Input Voltage HIGH State | RX output status HIGH | 0.60VS | | VS | V |
| $V_{K_{hys}}$ | Input Threshold Hysteresis | $V_{K_{high}} - V_{K_{low}}$ $V_S \geq 8.0V$ $V_S \geq 6.0V$ | 0.2 0.08 | 0.05VS | 1.0 | V V |
| $I_{K_{OFF}}$ | Input Current | $V_{TX} \geq V_{TX_{high}}$ $V_S, V_{CC} \geq 0V$ or $V_S,$ $V_{CC} = \text{open}$ or $GND = \text{open}$ | -5 | 4 | 40 | μA |
| $R_{K_{ON}}$ | Output ON Impedance | @ $V_S \geq 6.5V$ $V_{TX} \leq V_{TX_{low}}$ $I_K \geq 7mA$ 1) | | 10 | 30 | Ω |
| $I_{K_{SC}}$ | Short Circuit Current | $V_S \geq 6.5V$ | 40 | 60 | 150 | mA |
| $V_{K_{sat}}$ | Output Saturation Voltage | $R_{KO} = 1.5K\Omega$ | | | 1 | V |
| $V_{TX_{low}}$ | Input Voltage LOW State | | -24 | | 1 | V |
| $V_{TX_{high}}$ | Input Voltage HIGH State | | 3.5 | | VCC | V |
| $RR_{X_{ON}}$ RLO_{ON} | Output ON Impedance | $V_K \leq V_{K_{low}}; V_{LI} \leq V_{LI_{low}}$ $V_S \geq 6.5V; I_{RX,LO} \geq 1mA$ | | 40 | 90 | Ω |
| $VR_{X_{sat}}$ VLO_{sat} | Saturation Output Voltage | No external load | | | 1 | V |
| $IR_{X_{SC}}$ ILO_{SC} | Output short circuit current | $V_S \geq 6.5V$ | 9 | 20 | 50 | mA |
| RTX | Input pull up resistance | Output status = (HIGH) $T_A \leq 85^\circ C$ $-0.15V \leq V_{LO} \leq V_{CC} + 0.15V$ $-0.15V \leq V_{RX} \leq V_{CC} + 0.15V$ | 5 | 10 | 18 | k Ω |
| RTX | Input pull up resistance | $-0.15V \leq V_{TX} \leq V_{CC} + 0.15V$ $T_{amb} \leq 125^\circ C$ | 10 | 20 | 40 | k Ω |
| $V_{LI_{low}}$ | Input voltage LOW state | LO output status LOW | -24 | | 0.40VS | V |
| $V_{LI_{high}}$ | Input voltage HIGH state | LO output status HIGH | 0.60VS | | VS | V |
| ILI | Input current | $V_S, V_{CC} \geq 0V$ or $V_S, V_{CC} = \text{open}$ or $GND = \text{open}$ | -5 | 4 | 40 | μA |

Note 1) For external supplied output currents lower than this value a series protection diode can become active. See also Fig. 4 and 5.

ELECTRICAL CHARACTERISTICS (continued)

| Symbol | Parameter | Test Condition | Min. | Typ. | Max. | Unit |
|---|----------------------------|---|------|------|------|---------|
| $C_{KI,LO,RX}$ | Internal output capacities | | | | 20 | pF |
| f_{LI-LO} f_{K-RX} f_{TX-K} | Transmission frequency | $9V < V_S < 16V$, (external loads) $T_{min} \geq 20 \cdot R_{KO} \cdot C_K - K_{line}$ | 130 | | | kHz |
| f_{LI-LO} f_{K-RX} f_{TX-K} | Rise Time | for the definition of t_r , t_f see FIG. 1, 2) | | 0.4 | 2 | μs |
| | Fall Time | $9V < V_S < 16V$, (external loads) $T_{min} \geq 20 \cdot R_{KO} \cdot C_K - K_{line}$ | | 0.4 | 2 | μs |
| $t_{OFF,LI-LO}$ $t_{OFF,K-RX}$ $t_{OFF,TX-K}$ | Switch OFF time | for the definition of t_r , t_f see FIG. 1 | | 1.3 | 3 | μs |
| $t_{ON,LI-LO}$ $t_{ON,K-RX}$ $t_{ON,TX-K}$ | Switch ON time | $9V < V_S < 16V$, (external loads) $T_{min} \geq 20 \cdot R_{KO} \cdot C_K - K_{line}$ | | 1.3 | 3 | μs |
| $t_{dSB ON}$ $t_{dSB OFF}$ | Standby reaction time | $V_{TX} = 0V, I_K \geq 7mA$ $V_{LI} = 0V, 9V < V_S < 16V$ see FIG. 2 | | 10 | 20 | μs |
| | | | | 20 | 40 | μs |

Note 2) Speed limitation related to external capacitance $C_{ext RX, LO}$ and internal impedance $C_{LO, RX, RLO, RRX}$ for rise time.

$$t_r = R_{LO, RX} \cdot (C_{LO, RX} + C_{ext RX, LO}) \cdot 1.38.$$

Note 3) In case of spikes on $V_{CC} \geq 0.5V$ KOUT will be switched On for typical $10\mu s$ which represents the standby t_{dSB} reaction time.

FUNCTIONAL DESCRIPTION

The L9613B is a monolithic bus driver designed to provide bidirectional serial communication in automotive applications.

The device provides a bidirectional link, called K, to the V_{Bat} related diagnosis bus. It also includes a separate comparator L which is also able to be linked to the V_{Bat} bus. The input TX and output RX of K are related to V_{CC} with her integrated pull up resistances. Also the L comparator output LO has a pull up resistance connected to V_{CC} .

All V_{Bat} bus defined inputs LI and K have supply voltage dependent thresholds together with sufficient hysteresis to suppress line spikes. These pins are protected against overvoltages, shorts to GND and V_S and can also be driven beyond V_S and GND. These features are also given for TX, RX and LI only taking into account the behaviour of the internal pull up resistances. The thermal shut down function switches OFF the K output if the chip temperature increases above the thermal shut down threshold. To reactivate K again the chip temperature must decrease below the K switch ON temp. To achieve no fault for V_S undervoltage conditions the outputs will be switched OFF and stay at high impedance. The device is also protected against reverse battery condition. During lack of V_S or GND all pins shows high impedance characteristic. To realize a lack of the V_S related bus line LI and K the outputs LO and RX shows defined ON status. Suppressing all 4 classes of "Schaffner" signals (Schaffner 1; 2; 3a,b; 4) all pins can be load with short energy pulses of max. $\pm 0.2mJ$. All these features together with a high possible baud rate $>130Kbaud$, controlled output slopes for low EMI, a wide power supply voltage range and a real standby function with zero power consumption $I_{dSB typ} \leq 1\mu A$ during system depowering $V_{CC} \leq 0.5V$ make this device high efficient for automotive bus system.

After wake up of the system from SB condition the first output signal will have an additional delay time $t_{dtyp} \leq 5\mu s$.

The typical output voltage behaviour for the K, LO, RX outputs as a function of the output current is shown in Fig.5. Fig.6 shows a waveform of the output signal when the low level changes from $R_{ON} \cdot I_{OUT}$ to $I_{OUT} \cdot 2 \cdot R_{ON} + U_{BE}$ state. This variation occurs due to too low output current or after a negative transient forced to the output or to the supply voltage line.

Figure 1. Input to output timings and output pulse shape




Figure 2. Standby reaction time.




Figure 3. Output characteristics at K, LO, RX.




Figure 4. Output signal shape related to output current.




Figure 5. Standby current consumption.





Figure 6. Application Circuit.



EMS Performance (ISO 9141 BUS system)

Figure 7.





Figure 8.




ESD application hints

To improve the ESD robustness of this device above specified $\pm 2\text{KV}/\text{HBM}$ external blocking capacitors must be used. Nevertheless the max. energy which can be clamped by this device should not exceeds 0.2mJ for each pin. An equivalent input diagram for calculation can be seen in fig. 9.

ESD discharge model


$$E_{\text{ESD}} = \frac{1}{2} C_{\text{HBM}} U_{\text{ESD}}^2 = 0.2\text{mJ} + \frac{1}{2} C_{\text{EXT}} \cdot (45\text{V})^2$$

Figure 9.




| DIM. | mm | | | inch | | |
|-------|------------|------|------|-------|-------|-------|
| | MIN. | TYP. | MAX. | MIN. | TYP. | MAX. |
| A | | | 1.75 | | | 0.069 |
| a1 | 0.1 | | 0.25 | 0.004 | | 0.010 |
| a2 | | | 1.65 | | | 0.065 |
| a3 | 0.65 | | 0.85 | 0.026 | | 0.033 |
| b | 0.35 | | 0.48 | 0.014 | | 0.019 |
| b1 | 0.19 | | 0.25 | 0.007 | | 0.010 |
| C | 0.25 | | 0.5 | 0.010 | | 0.020 |
| c1 | 45° (typ.) | | | | | |
| D (1) | 4.8 | | 5.0 | 0.189 | | 0.197 |
| E | 5.8 | | 6.2 | 0.228 | | 0.244 |
| e | | 1.27 | | | 0.050 | |
| e3 | | 3.81 | | | 0.150 | |
| F (1) | 3.8 | | 4.0 | 0.15 | | 0.157 |
| L | 0.4 | | 1.27 | 0.016 | | 0.050 |
| M | | | 0.6 | | | 0.024 |
| S | 8° (max.) | | | | | |

OUTLINE AND MECHANICAL DATA



SO8

(1) D and F do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm (.006inch).



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco -
Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.