

深圳市维拓精电科技有限公司 WTL International Limited

APPROVAL SHEET

DESCRIPTION :	49S 0.20T INSULATION			
VERSION:	1			
DATE:	2018.10.09			
Customer	Customer P/N			
platan	/			
Customer Signature	WTL			
	Approved by: <i>Xo Xo Lee</i>			
	Checked by: <i>Susan He</i>			
	Issued by: <i>Shengbiao</i>			
REVISION HISTORY				
Revised Page	Revision Content	Date	Ref. No.	Reviser



49S 0.20T INSULATION

1、SPECIFICATIONS

Hold Style	49S 0.20T
Ingredient	PTFE
Color	White
Density g/cm ³	2.30
Tensile strength MPa	3 Min
Surface receptivity Ω	1X10 ¹³
Volume Impedance Ω	1X10 ¹⁶
Dielectric constant 10Hz	1.8-2.2
Thermal resistance $^{\circ}\text{C}$	260 10s Min
RoHS/Reach	Meet the requirements of RoHS and Reach regulations

REMARK:

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. PLEASE CONFIRM WITH OUR SALES ENGINEER.

2、DIMENSIONS (Unit: mm)

